



TIRES ARE SUBJECT TO AVAILABILITY



Size	Lbs	ADVAN A005/SLICK			ADVAN A006/WET	OVERALL DIAMETER		SECTION WIDTH		RECOMMENDED RIM WIDTH
		Article/Part No. Soft - A40	Article/Part No. Medium - A60	Article/Part No. Hard - A80	Article/Part No. W40/W60/W80	Inches	mm	Inches	mm	Width Range/Ideal
Porsche Cup Cars & GT Cars										
330/710R18	28	N2888/13035	N2889/13009	N2890/13002		27.87	708	13.98	355	12-14/13
				N2736/00711		27.80	706	14.02	356	12-14/13
320/710R18					N2924/00713					
300/680R18		N2855/Not available	N2856/13026	N2857/13027	W60-N2791/13043	26.85	682	13.07	332	11-13/12
280/680R18	24	N2270/Not available	N3113/13032	N2595/00683	N2496/00654	26.85	682	11.77	299	10-12/11
280/680R18					N2784/00722					
320/650R18			N3139/13022			25.75	654	13.43	341	12-14/13
300/650R18	23	N2844/13028	N2845/13003	N2846/13008	N2790/13045	25.59	650	12.99	330	11-13/12
280/650R18		N3141/13033	N3066/13034	N3063/13001	W40-N2815/13040	25.55	649	11.93	303	10-12/11
280/650R18	23		N2782/00704		N2923/00712	25.55	649	11.93	303	10-12/11
250/650R18	22	N2472/00691	N2596/13006	N2372/00667	N2320/00642	25.59	650	10.75	273	9-11/10
250/650R18					W40-N3144/13037	25.71	653	10.63	270	9-11/10
250/640R18	22		N3140/13024		W60-N2704/00721	25.20	644	10.63	264	8.5-10.5/9.5
240/640R18	22		N2506/13023	N2708/00684	W60-N2502/00648	25.20	640	9.61	244	8-10/9
Ferrari										
330/710R19			N2894/13029		W60-N2793/13048	27.87	708	13.78	350	12-14/13
310/690R19	28	N3183	N3129/13021		W60-N2939/13046	27.05	687	11.73	298	10-12/11
300/680R19	28				W60-N2791/13043	26.89	683	13.03	331	
300/690R19	28		N3143/13020		N2908 W60	27.05	687	11.54	293	9.5-11.5/10.5
260/660R19	27	N3182	N3004/13030		W60-N2937/13038	25.98	660	9.84	250	8-10/9
240/660R19	26		N3130/13017		W60-N2907/13036	25.79	655	9.10	230	8

GENERAL TECHNICAL INFORMATION

	Front	Rear
Camber - Min/Max	-2.5/-4.8	-1.5/-3.8
PSI Range - Cold/Hot	19-23/26-30	19-23/26-30
Temperature Range	180-220	180-220

Above specifications are recommended for a wide variety of vehicles and conditions and should be used as broad guidelines.

Indicates a spec tire



TIRES ARE SUBJECT TO AVAILABILITY



Size	Lbs	ADVAN A005/SLICK			ADVAN A006/WET	OVERALL DIAMETER		SECTION WIDTH		RECOMMENDED RIM WIDTH
		Article/Part No. Soft - A40	Article/Part No. Medium - A60	Article/Part No. Hard - A80	Article/Part No. W40/W60/W80	Inches	mm	Inches	mm	Width Range/Ideal
GTR Car										
290/710R20	28			N2613/00714		27.83	707	11.97	304	10-12/11
Touring Cars										
230/650R18		N2221/00581 super soft N2076-00582- soft	N2391	N2090		25.59	650	9.72	247	8-10/9
260/640R17			N2392/00593	N2393		25.20	640	10.83	275	9-11/10
240/640R17			N2394/00560	N2395	N2398/00605	25.20	640	9.96	253	8-10/9
240/640R17			N2953/00715			25.31	643	9.45	240	8.5-10.5/9.5
230/640R17-A054			N3034/13007			25.43	646	9.33	237	8
230/625R17			N2383/00554	N2384		24.41	620	9.72	247	8
210/610R17		N2203/00651	N2614/13005	N2202/13052	H N2610/13004	23.94	608	8.82	224	8
185/650R15		P30/L-N3125 /13059	P50/L-N3123/13061			25.51	648	8.82	224	7
185/650R15		P30/R-N3124/13060	P50/R-N3122/13062			25.51	648	8.82	224	7
185/650R15		A30/L-N3027/13011	A50/L-N3029/13013			25.51	648	8.82	224	7
185/650R15		A30/R-N3028/13012	A50/R-N3030/13014			25.51	648	8.82	224	7
240/45R13		N3006/13050			S - N3127/13051	22.72	577	10.94	278	9-11/10
180/50VR13		N3048/13049			N2132/00627	22.01	559	8.82	224	8

GENERAL TECHNICAL INFORMATION		
	Front	Rear
Camber - Min/Max	-2.5/-4.8	-1.5/-3.8
PSI Range - Cold/Hot	19-23/26-30	19-23/26-30
Temperature Range	180-220	180-220

Above specifications are recommended for a wide variety of vehicles and conditions and should be used as broad guidelines.

Touring car sizes are offered in (super soft/soft/medium/hard) currently this is our only 18 " touring car size
Rally Cross A054 - GROOVED -
A005 GRC Spec Slick for 2014/2015 season - N2953/00715
 P=Premium Spec (P30 soft/P50 Medium/P70 Hard) - A053 also has spec A30/A50/A70