



Size	ADVAN A005/SLICK			ADVAN A006/RAIN		OVERALL DIAMETER		SECTION WIDTH		RECOMMENDED RIM WIDTH
	Soft Article/Part No. A40	Medium Article/Part No. A60	Hard Article/Part No. A80	Rain Article/Part No. W40/W60/W80	Inches	mm	Inches	mm	Width Range/Ideal	
<b>Porsche Cup Cars &amp; GT Cars</b>										
330/710R18	N2888/13035	N2889/13009	N2890/13002		27.87	708	13.98	355	12-14/13	
			<b>N2736/00711</b>		27.80	706	14.02	356	12-14/13	
			80 + N3311/13300							
320/710R18				<b>N2924/00713</b>						
300/680R18	N2855/13025	N2856/13026	N2857/13027	W60-N2791/13043	26.85	682	13.07	332	11-13/12	
280/680R18	N2270/13031	N3113/13032	<b>N2595/00683</b>	N2496/00654	26.85	682	11.77	299	10-12/11	
280/680R18				<b>N2784/00722</b>						
320/650R18		N3139/13022			25.75	654	13.43	341	12-14/13	
300/650R18	N2844/13028	<b>N2845/13003</b>	<b>N2846/13008</b>	<b>N2790/13045</b>	25.59	650	12.99	330	11-13/12	
280/650R18	N3141/13033	N3066/13034	N3063/13001	W40-N2815/13040	25.55	649	11.93	303	10-12/11	
280/650R18		<b>N2782/00704</b>		<b>N2923/00712</b>	25.55	649	11.93	303	10-12/11	
250/650R18	N2472/00691	<b>N2596/13006</b>	N2372/00667	<b>N2320/00642</b>	25.59	650	10.75	273	9-11/10	
250/650R18				W40-N3144/13037	25.71	653	10.63	270	9-11/10	
250/640R18		N3140/13024		W60-N2704/00721	25.20	644	10.63	264	8.5-10.5/9.5	
240/640R18		N2506/13023	N2708/00684	W60-N2502/00648	25.20	640	9.61	244	8-10/9	
<b>Ferrari</b>										
330/710R19		N2894/13029		W60-N2793/13048	27.87	708	13.78	350	12-14/13	
310/690R19	N3183	N3129/13021		W60-N2939/13046	27.05	687	11.73	298	10-12/11	
300/680R19				W60-N2791/13043	26.89	683	13.03	331		
300/690R19		N3143/13020		N2908 W60	27.05	687	11.54	293	9.5-11.5/10.5	
260/660R19	N3182	N3004/13030		W60-N2937/13038	25.98	660	9.84	250	8-10/9	
240/660R19		N3130/13017		W60-N2907/13036	25.79	655	9.10	230	8	

**TECHINICAL INFORMATION**

	Front	Rear
Camber - Min/Max	-2.5/-4.8	-1.5/-3.8
PSI Range - Cold/Hot	19-23/26-30	19-23/26-30
Temperature Range	180-220	180-220

*Above specifications are recommended for a wide variety of vehicles and conditions and should be used as broad guidelines.*

Indicates a spec tire