



Size	ADVAN A005/SLICK			ADVAN A006/RAIN	OVERALL DIAMETER		SECTION WIDTH		RECOMMENDED RIM WIDTH
	Soft Article/Part No. A40	Medium Article/Part No. A60	Hard Article/Part No. A80	Rain Article/Part No. W40/W60/W80	Inches	mm	Inches	mm	Width Range/Ideal
330/710R18	N2888/13035	N2889/13009	N2890/13002		27.87	708	13.98	355	12-14/13
			80+ N3311/13300						
			N2736/00711		27.80	706	14.02	356	12-14/13
			N3382/13404						
320/710R18				N2924/00713					
300/680R18	N2855/13025	N2856/13026	N2857/13027	W60-N2791/13043	26.85	682	13.07	332	11-13/12
280/680R18	N2270/13031	N3113/13032	N2595/00683	N2784/00722	26.85	682	11.77	299	10-12/11
			N3420/13412		26.85	682	11.65	296	10.5
320/650R18	N/A	N3139/13022	N/A		25.75	654	13.43	341	12-14/13
300/650R18	N2844/13028	N2845/13003	N2846/13008	N2790/13045	25.59	650	12.99	330	11-13/12
		N3381/13403							
280/650R18	N3141/13033	N3066/13034	N3063/13001		25.55	649	11.93	303	10-12/11
		N2782/00704		N2923/00712	25.55	649	11.93	303	10-12/11
250/650R18	N2472/00691	N2596/13006	N2372/00667	N2320/00642	25.59	650	10.75	273	9-11/10
			N3419/13411		25.70	653	10.20	259	9
250/640R18	N/A	N3140/13024	N/A	W60-N2704/00721	25.20	644	10.63	264	8.5-10.5/9.5
330/710R19		N2894/13029		W60-N2793/13048	27.87	708	13.78	350	12-14/13
310/690R19	NA/N3183	N3129/13021		W60-N2939/13046	27.05	687	11.73	298	10-12/11
300/690R19		N3143/13020		W60-N2908/13010	27.05	687	11.54	293	9.5-11.5/10.5
260/660R19	NA/N3182	N3004/13030		W60-N2937/13038	25.98	660	9.84	250	8-10/9
240/660R19		N3130/13017		W60-N2907/13036	25.79	655	9.10	230	8

GENERAL TECHNICAL GUIDELINES		
	Front	Rear
Camber - Min/Max	-2.5/-4.8	-1.5/-3.8
PSI Range - Cold/Hot	18-23/26-30	17-23/26-30
Temperature Range	180-220	180-220
<i>Specifications are recommended for a wide variety of vehicles, conditions and should be used as broad guidelines.</i>		

Blue Ink represents 2025 pro spec tire
 Green Ink represents RFID pro spec tire
 Purple Ink represents 2026 wet pro spec (no change from the 2025 spec)